

1. PRODUCT AND COMPANY IDENTIFICATION

Product name RezRok 150 Epoxy Floor Patching Mortar - Resin/Side A
Version # 1.0
Revision date 18-Jun-2008
Company information PolySpec
 6614 Gant Road
 Houston, TX 77066 US
Emergency Chemtrec (800) 424-9300
 International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Bisphenol-A-(Epichlorohydrin) polymer	25068-38-6	< 90
Non-hazardous and other components below reportable levels		> 10
Composition comments	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

3. HAZARDS IDENTIFICATION

Emergency overview Irritating to eyes. May cause sensitization by skin contact. Irritating to skin.
Potential short term health effects
Eyes Causes eye irritation.
Skin Irritating to skin. May cause sensitization by skin contact.
Inhalation May cause irritation of respiratory tract.
Ingestion Do not ingest.

4. FIRST AID MEASURES

First aid
Eye contact Immediately flush eyes with plenty of water for at least 20 minutes.
Skin contact Remove and isolate contaminated clothing and shoes. If skin irritation persists, call a physician. Wash off immediately with plenty of water. Immediately flush skin with running water for at least 20 minutes.
Inhalation Call a physician if symptoms develop or persist. If breathing is difficult, give oxygen.
Ingestion Drink plenty of water. Do not induce vomiting without medical advice.
General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off contaminated clothing and shoes immediately. If you feel unwell, seek medical advice (show the label where possible).

5. FIRE FIGHTING MEASURES

Suitable extinguishing media Small Fires: Dry chemical, CO2, water spray or regular foam.
 Large Fires: Water spray, fog or regular foam.
Fire fighting equipment/instructions Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.
Flash point 480 °F (248.9 °C) Pensky-Martens Closed Cup

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures Stay upwind. Keep out of low areas. Keep unnecessary personnel away.
Containment procedures Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.

Personal precautions	Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for cleaning up	Avoid dust formation. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original containers for re-use.

7. HANDLING AND STORAGE

Handling	Wear personal protective equipment. Avoid contact with eyes. Do not get this material in contact with skin or eyes. Do not handle or store near an open flame, heat or other sources of ignition. Surfaces may become slippery after spillage.
Storage	Keep in a cool, well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment	
Respiratory protection	In case of insufficient ventilation wear suitable respiratory equipment. No personal respiratory protective equipment normally required.
Hand protection	Protective gloves.
Eye protection	Wear chemical goggles. Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves. Wear suitable protective clothing.
General	Avoid contact with the skin and the eyes.
Engineering measures to reduce exposure	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Hygiene measures	Avoid contact with the skin and the eyes. Handle in accordance with good industrial hygiene and safety practice. When using do not smoke.

9. PHYSICAL & CHEMICAL PROPERTIES

Density	9.574 lb/gal
Form	Liquid.
Specific gravity	1.1489

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability	Stable at normal conditions.
Conditions to avoid	Direct sources of heat.
Incompatibility	None known.

11. TOXICOLOGICAL INFORMATION

Local effects	Irritating to eyes. Irritating to skin. May cause sensitization by skin contact.
Component analysis - LD50	
NIOSH - Selected LD50s and LC50s	
Bisphenol-A-(Epichlorohydrin) polymer	25068-38-6 Oral LD50 Rat: 11400 mg/kg; Oral LD50 Mouse: 15600 mg/kg
Sensitization	May cause sensitization by skin contact.
Routes of exposure	Skin contact.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Components of this product have been identified as having potential environmental concerns.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Disposal instructions

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. TRANSPORTATION INFORMATION

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

International Air Transport Association (IATA) Requirements

Not regulated as dangerous goods.

International Maritime Dangerous Goods (IMDG) Code Requirements

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Inventory - United States - Section 8(b) Inventory (TSCA)

Bisphenol-A-(Epichlorohydrin) polymer 25068-38-6 XU

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (superfund) reportable quantity

None

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

NFPA ratings

Health: 1
Flammability: 1
Instability: 0

16. OTHER INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Issue date

18-Jun-2008