

MATERIAL SAFETY DATA SHEET

Health: 1 Flammability: 1 Physical hazard: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name RezRok 150 Epoxy Floor Patching Mortar - Hardener/Side B

Version # 1.0

Revision date 29-Jan-2008 PolySpec Company information

6614 Gant Road Houston, TX 77066 US

Chemtrec (800) 424-9300 **Emergency**

International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

The manufacturer lists no ingredients as hazardous according to OSHA 29 CFR 1910.1200.

Composition comments This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

3. HAZARDS IDENTIFICATION

Health injuries are not known or expected under normal use. **Emergency overview**

Potential short term health effects

Eves Contact with eyes may cause irritation. Skin Not expected to be a primary skin irritant. Inhalation May cause irritation of respiratory tract. Ingestion Do not ingest. May be harmful if swallowed.

4. FIRST AID MEASURES

First aid

Flush eyes with water as a precaution. If irritation persists get medical attention. Eye contact

Skin contact Rinse with water. Get medical attention if irritation develops or persists.

Inhalation Call a physician if symptoms develop or persist. If breathing is difficult, give oxygen.

Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. Ingestion If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of

a large amount does occur, seek medical attention.

General advice If you feel unwell, seek medical advice (show the label where possible).

5. FIRE FIGHTING MEASURES

Small Fires: Dry chemical, CO2, water spray or regular foam. Suitable extinguishing media

Large Fires: Water spray, fog or regular foam.

Fire fighting

equipment/instructions

Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in

flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Flash point 200 °F (93.3 °C) Pensky-Martens Closed Cup

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures Keep unnecessary personnel away.

Containment procedures Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Absorb with earth, sand or other non-combustible material and transfer to containers for later Methods for cleaning up

disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original

containers for re-use.

Product name: RezRok 150 Epoxy Floor Patching Mortar - Hardener/Side B Material ID: 709 Version #: 1.0 Revision date: 29-JAN-2008 Print date: 29-JAN-2008

7. HANDLING AND STORAGE

Handling Do not handle or store near an open flame, heat or other sources of ignition. Handle and open

container with care. Surfaces may become slippery after spillage.

Keep in a cool, well-ventilated place. This material can accumulate static charge which may **Storage**

cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Use care in handling/storage. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment

In case of insufficient ventilation wear suitable respiratory equipment. No personal respiratory Respiratory protection

protective equipment normally required.

Avoid contact with eyes. Eye protection

Wear suitable protective clothing Skin and body protection Wear suitable protective equipment. General

Hygiene measures When using do not smoke. Handle in accordance with good industrial hygiene and safety

practice.

9. PHYSICAL & CHEMICAL PROPERTIES

7.9271 lb/gal **Density** Liquid. **Form** Specific gravity 0.9512

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability Stable at normal conditions. Conditions to avoid Direct sources of heat.

Incompatibility Acids. Alcohols. Cresol. Glycol. Isocyanates. Phenol. Strong oxidizing agents. Vinyl acetates.

Will form explosive mixtures in air.

11. TOXICOLOGICAL INFORMATION

Further information This product has no known adverse effect on human health.

12. ECOLOGICAL INFORMATION

Ecotoxicity This material is not expected to be harmful to aquatic life.

13. DISPOSAL CONSIDERATIONS

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions**

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA

criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. TRANSPORTATION INFORMATION

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

International Air Transport Association (IATA) Requirements

Not regulated as dangerous goods.

International Maritime Dangerous Goods (IMDG) Code Requirements

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Product name: RezRok 150 Epoxy Floor Patching Mortar - Hardener/Side B

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 No

hazardous chemical

CERCLA (superfund) reportable quantity

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely

No hazardous substance

Section 311 hazardous

chemical

No

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

NFPA ratings Health: 1

Flammability: 1 Instability: 0

16. OTHER INFORMATION

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Issue date 29-Jan-2008