

MATERIAL SAFETY DATA SHEET

Health: 0* Flammability: 1 Physical hazard: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name Thiokol 2235M Polysulfide Joint Sealant - Resin/Side A

Version # 1.0

Revision date 14-Jun-2011

Company information ITW PolySpec Thiokol

6614 Gant Road

Houston, TX 77066 US

Emergency Chemtrec (800) 424-9300

International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS#	Percent
Calcium carbonate	1317-65-3	< 40
Titanium dioxide	13463-67-7	< 10
Non-hazardous and other components below reportable levels		> 60

3. HAZARDS IDENTIFICATION

Emergency overview Harmful in contact with eyes. Danger of serious damage to health by prolonged exposure. May

cause cancer. May cause breathing disorders and lung damage.

Potential short term health effects

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Components of the product may be absorbed into the body through the skin.

Inhalation May cause breathing disorders and lung damage.

Ingestion Do not ingest.

Target organs Eyes. Lungs. Respiratory system. Skin.

4. FIRST AID MEASURES

First aid

Eye contact Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention

immediately. Get medical attention if irritation develops or persists.

Skin contact Get medical attention immediately. Remove and isolate contaminated clothing and shoes.

Immediately flush skin with running water for at least 20 minutes. For minor skin contact, avoid spreading material on unaffected skin. Wash off immediately with plenty of water. If skin

irritation persists, call a physician.

Inhalation Get medical attention immediately. Move to fresh air. Oxygen or artificial respiration if needed.

Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, give oxygen. Get medical attention, if needed.

Ingestion If material is ingested, immediately contact a physician or poison control center. Do not induce

vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth

method if victim ingested the substance.

Notes to physician Symptoms may be delayed.

General advice Keep victim warm. Keep victim under observation. In case of shortness of breath, give oxygen.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media Small Fires: Dry chemical, CO2, water spray or regular foam.

Large Fires: Water spray, fog or regular foam.

Product name: Thiokol 2235M Polysulfide Joint Sealant - Resin/Side A

Material ID: 805 Version #: 1.0 Revision date: 14-JUN-2011 Print date: 14-JUN-2011

Fire fightingMove containers from fire area if you can do it without risk. Do not scatter spilled material with equipment/instructions
high pressure water streams. Withdraw immediately in case of rising sound from venting safety

high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all

directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Flash point 200 °F (93.3 °C) Pensky-Martens Closed Cup

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures Stay upwind. Keep out of low areas. Keep unnecessary personnel away.

Containment procedures Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Prevent entry into waterways, sewers, basements or confined areas.

Personal precautions Do not touch or walk through spilled material. Do not touch damaged containers or spilled

material unless wearing appropriate protective clothing. Keep people away from and upwind of

spill/leak.

Methods for cleaning up Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original

containers for re-use.

7. HANDLING AND STORAGE

Handling Do not breathe gas/fumes/vapor/spray. Wear personal protective equipment. Do not handle or

store near an open flame, heat or other sources of ignition. Surfaces may become slippery

after spillage.

Storage Keep container tightly closed. Keep out of the reach of children. Keep in a cool, well-ventilated

place. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding

techniques. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

ACGIH - Threshold Limits Values - Time Weighted Averages (TLV-TWA)
Titanium dioxide 13463-67-7 10 Mg/m3 TWA
ACGIH - Threshold Limits Values - TLV Basis - Critical Effects

Titanium dioxide 13463-67-7 lung OSHA - Final PELs - Time Weighted Averages (TWAs)

Calcium carbonate 1317-65-3 15 Mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

Titanium dioxide 13463-67-7 15 Mg/m3 TWA (total dust)

Personal protective equipment

Respiratory protection A NIOSH- approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. In case of insufficient ventilation wear suitable respiratory equipment.

Hand protection Protective gloves.

Eye protection Wear chemical goggles.

Skin and body protection Wear suitable protective clothing.

General Avoid contact with the skin and the eyes.

Engineering measures to

reduce exposure

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Hygiene measures Keep away from food and drink. Handle in accordance with good industrial hygiene and safety

practice for diagnostics. When using do not smoke. Handle in accordance with good industrial

hygiene and safety practice.

9. PHYSICAL & CHEMICAL PROPERTIES

Density13.08 lb/galFormLiquid.Specific gravity1.57

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

StabilityStable at normal conditions.Conditions to avoidDirect sources of heat.

Hazardous polymerization Will not occur.

2/4

Incompatibility Fluorine.

11. TOXICOLOGICAL INFORMATION

Local effects Risk of serious damage to eyes. Components of the product may be absorbed into the body

through the skin.

Carcinogenicity Cancer hazard. **ACGIH - Threshold Limits Values - Carcinogens**

Titanium dioxide 13463-67-7 A4 - Not Classifiable as a Human Carcinogen **Chronic toxicity** Prolonged or repeated exposure may cause lung injury.

12. ECOLOGICAL INFORMATION

Ecotoxicity Components of this product have been identified as having potential environmental concerns.

13. DISPOSAL CONSIDERATIONS

Disposal instructions This product, in its present state, when discarded or disposed of, is not a hazardous waste

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. TRANSPORTATION INFORMATION

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

ERG number 138

International Air Transport Association (IATA) Requirements

Not regulated as dangerous goods.

International Maritime Dangerous Goods (IMDG) Code Requirements

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

Inventory - European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

215-279-6 Calcium carbonate 1317-65-3 236-675-5 Titanium dioxide 13463-67-7 Inventory - United States - Section 8(b) Inventory (TSCA) Calcium carbonate 1317-65-3 Present 13463-67-7 Titanium dioxide Present

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 Yes

hazardous chemical

CERCLA (superfund) reportable quantity

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely hazardous substance

No

Section 311 hazardous

Yes

chemical

Immediate Hazard - No. **Hazard categories**

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Product name: Thiokol 2235M Polysulfide Joint Sealant - Resin/Side A

NFPA ratings Health: 0 Flammability: 1

Instability: 0

State regulations

Massachusetts - Right To Know List

Calcium carbonate 1317-65-3 Present Titanium dioxide 13463-67-7 Present New Jersey - Right to Know Hazardous Substance List Titanium dioxide 13463-67-7 sn 1861

Pennsylvania - RTK (Right to Know) List

Calcium carbonate 1317-65-3 Present Titanium dioxide 13463-67-7 Present

16. OTHER INFORMATION

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

14-Jun-2011 Issue date

Hazards Identification: Emergency Overview MSDS sections updated

Hazards Identification: Eyes Hazards Identification: Skin Hazards Identification: Target organs Hazards Identification: Specific hazards First Aid Measures: Eye contact First Aid Measures: Skin contact

Exposure Controls / Personal Protection: Eye protection Chemical Stability & Reactivity Information: Incompatibility

Toxicological Information: Local effects

Product name: Thiokol 2235M Polysulfide Joint Sealant - Resin/Side A

Material ID: 805 Version #: 1.0 Revision date: 14-JUN-2011 Print date: 14-JUN-2011